

Vega Series

LED Batten



2 Year
WARRANTY

TECHNICAL SPECIFICATIONS

MODEL	WATTAGE	VOLTAGE	CURRENT	LUMEN	CCT(K)
LTL22W-CW	22W	120V~270V	0.096A	2640lm	6000K
LTL22W-MW	22W	120V~270V	0.096A	2640lm	4000K
LTL22W-WW	22W	120V~270V	0.096A	2640lm	3000K
LTL20W-CW	20W	120V~270V	0.087A	2400lm	6000K
LTL20W-MW	20W	120V~270V	0.087A	2400lm	4000K
LTL20W-WW	20W	120V~270V	0.087A	2400lm	3000K
LTL10W-CW	10W	120V~270V	0.043A	1200lm	6000K
LTL10W-MW	10W	120V~270V	0.043A	1200lm	4000K
LTL10W-WW	10W	120V~270V	0.043A	1200lm	3000K
LTL05W-CW	5W	120V~270V	0.022A	600lm	6000K
LTL05W-MW	5W	120V~270V	0.022A	600lm	4000K
LTL05W-WW	5W	120V~270V	0.022A	600lm	3000K

COLOUR TEMPERATURE



FEATURES

- LM80 Certified LEDs mounted on aluminium PCB for better heat dissipation, improved life and CCT maintenance.
- 26-28lm LEDs with less than 90% loading - suitable for continuous usage.
- 100% Virgin Polycarbonate Housing for long lasting performance & endurance
- Sustains 440VAC upto 12hrs - designed to withstand double-phase conditions.
- 4KVA In-built surge protection for better sustainability in lightning conditions.
- BIS Certified product, ISO 9001-2015 Certified Company

APPLICATIONS



PHYSICAL DIMENSIONS



WATTAGE (W)	LENGTH (X)	WIDTH (Y)	HEIGHT (Z)
22W	1180mm	25mm	38mm
20W	1180mm	25mm	38mm
10W	475mm	25mm	38mm
5W	235mm	25mm	38mm

